



SAFETY DATA SHEET

SDS ID NO.: 0101MAR019
Revision Date: 05/19/2015

1. IDENTIFICATION

Product Name: Marathon Petroleum Propane - All Grades
Synonym: Deodorized LPG; Unstented Propane, Unstented Propane Tfr
Chemical Family: Hydrocarbon Gas
Recommended Use: Fuel and Feedstock.
Use Restrictions: All others.

Supplier Name and Address:
MARATHON PETROLEUM COMPANY LP
539 South Main Street
Findlay, OH 45840

SDS information: 1-419-421-3070

Emergency Telephone: 1-877-627-5463

2. HAZARD IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous according to the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable gases	Category 1
Gases under pressure	Liquefied Gas
Simple Asphyxiant	-

Hazards Not Otherwise Classified (HNOC)

Static accumulating flammable liquid
Liquid product may cause freeze burn

Label elements

EMERGENCY OVERVIEW

Danger

Extremely flammable gas
Contains gas under pressure; may explode if heated
May accumulate electrostatic charge and ignite or explode
May displace oxygen and cause rapid suffocation
Contact with liquid product may cause freeze burn



Appearance Colorless Liquefied Gas

Physical State Liquefied Gas

Odor Odorless to rotten-egg like.

Precautionary Statements - Prevention

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Precautionary Statements - Response

Leaking gas fire: Do not extinguish, unless leak can be stopped safely
Eliminate all ignition sources if safe to do so

Precautionary Statements - Storage

Store in a well-ventilated place
Protect from sunlight

Precautionary Statements - Disposal

Dispose of contents/container at an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Propane is an aliphatic petroleum hydrocarbon.

Composition Information:

Name	CAS Number	Weight %
Propane	74-98-6	94-100
Propylene	115-07-1	0-3.5
Isobutane	75-28-5	0-2.5
n-Butane	106-97-8	0-2.5
Ethane	74-84-0	0-2
Methane	74-82-8	0-1.5
Sulfur containing compounds	7704-34-9	0-0.01

4. FIRST AID MEASURES

First Aid Measures

General advice

In case of accident or if you feel unwell, seek medical advice immediately (show directions for use or safety data sheet if possible).

Inhalation:

Remove to fresh air. If not breathing, institute rescue breathing. If breathing is difficult, ensure airway is clear, give oxygen and continue to monitor. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). GET IMMEDIATE MEDICAL ATTENTION.

Skin Contact:

If liquefied product has caused frostbite, remove contaminated clothing. Thaw frost bitten areas slowly with lukewarm water or by wrapping affected areas with blankets. Do not rub affected areas. Let circulation reestablish itself naturally, exercising area if possible. GET IMMEDIATE MEDICAL ATTENTION.

Eye Contact: Liquid: Flush with large amounts of tepid water for at least 15 minutes. If frostbite is suspected (cloudy lens or greyish white tissue around the eye), GET IMMEDIATE MEDICAL ATTENTION.
Gas: Call a physician if signs or symptoms of contact occur, including irritation.

Ingestion: Ingestion not likely. If swallowed, immediately call a physician.

Most important signs and symptoms, both short-term and delayed with overexposure

Adverse Effects: Asphyxiant gas. High concentrations in the immediate area can displace oxygen causing the feeling of suffocation and can cause headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue from oxygen deprivation.

Indication of any immediate medical attention and special treatment needed

NOTES TO PHYSICIAN: Treat symptomatically. Administer supplemental oxygen as needed. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed to this material. Administration of sympathomimetic drugs should be avoided.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

For small fires, Class B fire extinguishing media such as CO2 or dry chemical can be used. For large fires use water spray or fog. Firefighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.

Unsuitable extinguishing media

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific hazards arising from the chemical

This product has been determined to be an extremely flammable gas per the OSHA Hazard Communication Standard and should be handled accordingly. May accumulate electrostatic charge and ignite or explode. Sealed containers may rupture when heated. A phenomena known as boiling liquid expanding vapor explosions (Bleve) can occur when a liquid in a pressurized container comes in close proximity to a fire and reaches a temperature well above its boiling point. A catastrophic failure of the vessel can occur, resulting in flying equipment fragments, a shock wave and a fireball causing serious damage and death. For additional fire related information see NFPA 30 or North American Emergency Response Guide 115.

Hazardous combustion products

Smoke, carbon monoxide, and other products of incomplete combustion.

Explosion data

Sensitivity to Mechanical Impact No.
Sensitivity to Static Discharge Yes.

Special protective equipment and precautions for firefighters

Firefighters should wear full protective clothing and positive-pressure self-contained breathing apparatus (SCBA) with a full face-piece, as appropriate. Isolate hazard area. If safe to do so, stop the flow of gas and allow fire to burn out. Extinguishing the flame before shutting off the supply can cause the formation of explosive mixtures. In some cases it may be preferred to allow the flame to continue to burn. Use extreme caution when fighting liquefied petroleum gas fires. Keep surrounding area cool with water spray from a distance and prevent further ignition of combustible material. Avoid use of solid water streams. Contact with water and liquefied product can cause increased vaporization.

NFPA: Health 1 Flammability 4 Instability 1 Special Hazards -

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Keep people away from and upwind of spill/leak. Isolate and evacuate area. Shut off source if safe to do so. Distant ignition and flashback are possible. Eliminate all ignition sources. Use grounded and bonded, explosion-proof equipment. Monitor area for flammable or explosive atmosphere. Before entry, especially into confined areas, check atmosphere with an appropriate monitor.

- Protective Equipment:** Use personal protection measures as recommended in Section 8.
- Emergency Procedures:** Leaking containers should be moved outdoors or to well-ventilated area and contents transferred to a suitable container. Product vapor is heavier than air and can collect in low areas that are without sufficient ventilation. Notify local health and pollution control agencies, if appropriate.
- Environmental precautions:** If leaking, take appropriate steps to disperse gas.
- Methods and materials for containment:** Prevent further leakage or spillage if safe to do so.
- Methods and materials for cleaning up:** Shut off gas supply, if safe to do so. Isolate area until gas has dispersed.

7. HANDLING AND STORAGE

- Safe Handling Precautions:** Avoid breathing gas or mists. Use only with adequate ventilation. Gas may accumulate along the ground, settle in low lying areas or be moved by ventilation and ignited by many sources such as pilot lights, sparks, electric motors, static discharge, or other ignition sources at locations distant from material handling. Flashback may occur along vapor trails. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. Use only non-sparking tools Use appropriate grounding and bonding practices. Bonding and grounding may be insufficient to eliminate the hazard from static electricity. Do not cut, drill, grind or weld on empty containers since explosive residues may remain. Comply with all applicable EPA, OSHA, NFPA and consistent state and local requirements.
- Storage Conditions:** Product is stored as a liquid but used in the gaseous state. Store in properly closed containers that are appropriately labeled and in a cool, well-ventilated area. Keep product and empty container away from heat and sources of ignition. Do not puncture or incinerate container.
- Incompatible materials** Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	ACGIH TLV	OSHA PELs:	OSHA - Vacated PELs	NIOSH IDLH
Propane 74-98-6	Simple asphyxiant	TWA: 1000 ppm TWA: 1800 mg/m ³	1000 ppm TWA 1800 mg/m ³ TWA	2100 ppm
Propylene 115-07-1	500 ppm TWA	-	-	-
Isobutane 75-28-5	1000 ppm STEL	-	-	-
n-Butane 106-97-8	1000 ppm STEL	-	800 ppm TWA 1900 mg/m ³ TWA	-
Ethane 74-84-0	Simple asphyxiant	-	-	-
Methane 74-82-8	Simple asphyxiant	-	-	-
Sulfur containing compounds 7704-34-9	-	-	-	-

Notes: The manufacturer has voluntarily elected to provide exposure limits contained in OSHA's 1989 air contaminants standard in its SDSs, even though certain of those exposure limits were vacated in 1992.

Engineering measures: Local or general exhaust required in an enclosed area or when there is inadequate ventilation. Use mechanical ventilation equipment that is explosion-proof. Monitor atmospheric oxygen levels.

Personal protective equipment

Eye protection:	Goggles or faceshield may be needed when handling pressurized gases.
Skin and body protection:	Wear insulated gloves to prevent skin contact and frostbite or freeze burn. Contact the glove manufacturer for specific advice on glove selection and breakthrough times.
Respiratory protection:	Use atmosphere supplying respirators in the event of oxygen deficiency, when material produces vapors that exceed permissible limits, or when excessive vapors are generated. Observe respirator assigned protection factors (APFs) criteria cited in federal OSHA 29 CFR 1910.134. Note: Air purifying respirators are not to be used in atmospheres that exceed the maximum use concentration (as directed by regulation or the manufacturers instructions), in oxygen deficient atmospheres, (less than 19.5% oxygen) or under conditions that are immediately dangerous to life and health (IDLH).
Hygiene measures:	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Do not smoke while handling.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical State	Liquefied Gas
Appearance	Colorless Liquefied Gas
Color	Colorless
Odor	Odorless to rotten-egg like.
Odor Threshold	No available data.

<u>Property</u>	<u>Values (Method)</u>
Melting Point / Freezing Point	-187.8 °C / -306 °F
Initial Boiling Point / Boiling Range	-42 °C / -43.8 °F
Flash Point	-104 °C / -155 °F
Evaporation Rate	No available data.
Flammability (solid, gas)	Extremely flammable gas
Flammability Limit in Air (%)	
Upper Flammability Limit:	9.5
Lower Flammability Limit:	2.0
Vapor Pressure	105 psi @ 15°C
Vapor Density	1.55 (Air = 1)
Specific Gravity / Relative Density	0.5
Water Solubility	3.2 x 10 ⁻⁵ mole fraction @ 15 °C
Solubility in other solvents	No available data.
Partition Coefficient	No available data.
Decomposition temperature:	No available data.
pH:	Not applicable
Autoignition Temperature	450 °C / 842 °F
Kinematic Viscosity	No available data.
Dynamic Viscosity	No available data.
Explosive Properties	No available data.
Softening Point	No available data.
VOC Content (%)	No available data.
Density	31.6 lbs/gal 60°F
Bulk Density	Not applicable

10. STABILITY AND REACTIVITY**Reactivity**

The product is non-reactive under normal conditions.

<u>Chemical stability</u>	The material is stable at 70°F, 760 mmHg pressure.
<u>Possibility of hazardous reactions</u>	None under normal processing.
<u>Hazardous polymerization</u>	Does not polymerize except under special conditions (extreme temperatures, pressure, oxidizers).
<u>Conditions to avoid</u>	Sources of heat or ignition.
<u>Incompatible materials</u>	Strong oxidizing agents.
<u>Hazardous decomposition products</u>	None known under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Potential short-term adverse effects from overexposures

Inhalation	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. In high concentration the gas may cause suffocation. Victim may not be aware of asphyxiation.
Eye contact	Vapor is generally non-irritating to eyes. Direct contact with liquefied product can cause freeze burn or frostbite.
Skin contact	Vapor is generally non-irritating to skin. Direct contact with liquefied product can cause freeze burn or frostbite.
Ingestion	Ingestion not likely.

Acute Toxicological data

Name	Oral LD50	Dermal LD50	Inhalation LC50
Propane 74-98-6	-	-	> 1,464 mg/L (Rat) 15 min
Propylene 115-07-1	-	-	658 mg/L (Rat) 4 h
Isobutane 75-28-5	-	-	570,000 ppm (Rat) 15 min
n-Butane 106-97-8	-	-	658 mg/L (Rat) 4 h
Ethane 74-84-0	-	-	658 mg/L (Rat) 4 h
Methane 74-82-8	-	-	326 mg/m ³ (Mouse) 2 h
Sulfur containing compounds 7704-34-9	> 3000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 9.23 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

PROPANE: Studies in laboratory animals indicate exposure to extremely high levels of propane (1 to 10 vol.% in air) may cause cardiac arrhythmias (irregular heartbeats) which may be serious or fatal.

PROPYLENE: At extremely high levels propylene gas acts as a general anesthetic and central nervous system depressant. Studies in laboratory animals indicate evidence of mild, reversible hydrocarbon nephropathy in male rats exposed to levels of 1000-4,500 ppm propylene for 90-days. The International Agency for Research in Cancer (IARC) has determined that there is inadequate evidence in experimental animals for the carcinogenicity of propylene. Overall evaluation: Propylene is not classifiable as to its carcinogenicity to humans (Group 3).

BUTANES: Studies in laboratory animals indicate exposure to extremely high levels of butanes (1-10 or higher vol.% in air) may cause cardiac arrhythmias (irregular heartbeats) which may be serious or fatal.

METHANE and ETHANE: Exposure to high levels of these gases produce weak central nervous system (CNS) depressant effects without significant potential for systemic toxicity. At very high levels they act as asphyxiant gases by diluting and displacing oxygen. Symptoms of persons exposed to oxygen deficient atmospheres include headache, dizziness, incoordination, cyanosis and narcosis. Extremely high concentrations can produce unconsciousness followed by death.

Adverse effects related to the physical, chemical and toxicological characteristics

Signs & Symptoms Headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue.

Sensitization Not expected to be a skin or respiratory sensitizer.

Mutagenic effects None known.

Carcinogenicity Cancer designations are listed in the table below.

Name	ACGIH (Class)	IARC (Class)	NTP	OSHA
Propane 74-98-6	Not Listed	Not Listed	Not Listed	Not Listed
Propylene 115-07-1	Not Listed	Not Classifiable (3)	Not Listed	Not Listed
Isobutane 75-28-5	Not Listed	Not Listed	Not Listed	Not Listed
n-Butane 106-97-8	Not Listed	Not Listed	Not Listed	Not Listed
Ethane 74-84-0	Not Listed	Not Listed	Not Listed	Not Listed
Methane 74-82-8	Not Listed	Not Listed	Not Listed	Not Listed
Sulfur containing compounds 7704-34-9	Not Listed	Not Listed	Not Listed	Not Listed

Reproductive toxicity None known.

Specific Target Organ Toxicity (STOT) - single exposure Not classified.

Specific Target Organ Toxicity (STOT) - repeated exposure Not classified.

Aspiration hazard Not applicable.

12. ECOLOGICAL INFORMATION

Ecotoxicity Not classified in terms of aquatic toxicity.

Name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Propane 74-98-6	-	-	-	-
Propylene 115-07-1	-	-	-	-
Isobutane 75-28-5	-	-	-	-
n-Butane 106-97-8	-	-	-	-
Ethane 74-84-0	-	-	-	-
Methane 74-82-8	-	-	-	-
Sulfur containing compounds 7704-34-9	-	96-hr LC50 >10,000 mg/L Western mosquitofish 96-hr LC50 = 866 mg/L Zebrafish	-	-

Persistence and degradability Expected to be inherently biodegradable.

Bioaccumulation Not expected to bioaccumulate in aquatic organisms.

Mobility in soil Expected to rapidly partition to air.

Other adverse effects The aquatic 96 hour TLM for propane is >100 ppm.

13. DISPOSAL CONSIDERATIONS

Description of Waste Residues

No information available.

Safe Handling of Wastes

Handle in accordance with applicable local, state, and federal regulations. Use personal protection measures as required. Use appropriate grounding and bonding practices. Use only non-sparking tools. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. No smoking.

Disposal of Wastes / Methods of Disposal

The user is responsible for determining if any discarded material is a hazardous waste (40 CFR 262.11). Dispose of in accordance with federal, state and local regulations.

Methods of Contaminated Packaging Disposal

Empty containers should be completely drained and then discarded or recycled, if possible. Do not cut, drill, grind or weld on empty containers since explosive residues may be present. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT (49 CFR 172.101):

UN Proper shipping name:	Propane
UN/Identification No:	UN 1978
Transport Hazard Class(es):	2.1
Packing group:	Not applicable
DOT reportable quantity (lbs):	Not applicable

TDG (Canada):

UN Proper shipping name:	Propane
UN/Identification No:	UN 1978
Transport Hazard Class(es):	2.1

Packing group: Not applicable

15. REGULATORY INFORMATION

US Federal Regulatory Information:

US TSCA Chemical Inventory Section 8(b): This product and/or its components are listed on the TSCA Chemical Inventory.

EPA Superfund Amendment & Reauthorization Act (SARA):

SARA Section 302: This product does not contain any component(s) included on EPA's Extremely Hazardous Substance (EHS) List.

Name	CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs
Propane	NA
Propylene	NA
Isobutane	NA
n-Butane	NA
Ethane	NA
Methane	NA
Sulfur containing compounds	NA

SARA Section 304: This product does not contain any component(s) identified as an EHS or a CERCLA Hazardous substance, which in case of a spill or release may be subject to SARA reporting requirements.

Name	CERCLA/SARA - Hazardous Substances and their Reportable Quantities
Propane	NA
Propylene	NA
Isobutane	NA
n-Butane	NA
Ethane	NA
Methane	NA
Sulfur containing compounds	NA

SARA: The following EPA hazard categories apply to this product:

- Acute Health Hazard
- Fire Hazard
- Sudden Release Of Pressure

SARA Section 313: This product may contain component(s), which if in exceedance of the de minimis threshold, may be subject to the reporting requirements of SARA Title III Section 313 Toxic Release Reporting (Form R).

Name	CERCLA/SARA 313 Emission reporting:
Propane	None
Propylene	1.0 % de minimis concentration
Isobutane	None
n-Butane	None
Ethane	None
Methane	None
Sulfur containing compounds	None

State and Community Right-To-Know Regulations:

The following component(s) of this material are identified on the regulatory lists below:

Propane
Louisiana Right-To-Know: Not Listed.

California Proposition 65:	Not Listed.
New Jersey Right-To-Know:	SN 1594
Pennsylvania Right-To-Know:	Present
Massachusetts Right-To Know:	Present
Florida Substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic; Flammable
Michigan Critical Materials Register List:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed.
California - Regulated Carcinogens:	Not Listed.
Pennsylvania RTK - Special Hazardous Substances:	Not Listed.
New Jersey - Special Hazardous Substances:	Flammable - fourth degree
New Jersey - Environmental Hazardous Substances List:	SN 1594 TPQ: 500 lb
Illinois - Toxic Air Contaminants	Not Listed.
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed.
Propylene	
Louisiana Right-To-Know:	Not Listed.
California Proposition 65:	Not Listed.
New Jersey Right-To-Know:	SN 1609
Pennsylvania Right-To-Know:	Environmental hazard
Massachusetts Right-To Know:	Present
Florida Substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic; Flammable
Michigan Critical Materials Register List:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed.
California - Regulated Carcinogens:	Not Listed.
Pennsylvania RTK - Special Hazardous Substances:	Not Listed.
New Jersey - Special Hazardous Substances:	Flammable - fourth degree
New Jersey - Environmental Hazardous Substances List:	SN 1609 TPQ: 500 lb
Illinois - Toxic Air Contaminants	Not Listed.
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed.
Isobutane	
Louisiana Right-To-Know:	Not Listed.
California Proposition 65:	Not Listed.
New Jersey Right-To-Know:	SN 1040
Pennsylvania Right-To-Know:	Present
Massachusetts Right-To Know:	Present
Florida Substance List:	Not Listed.
Rhode Island Right-To-Know:	Not Listed.
Michigan Critical Materials Register List:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed.
California - Regulated Carcinogens:	Not Listed.
Pennsylvania RTK - Special Hazardous Substances:	Not Listed.
New Jersey - Special Hazardous Substances:	Flammable - fourth degree
New Jersey - Environmental Hazardous Substances List:	SN 1040 TPQ: 500 lb
Illinois - Toxic Air Contaminants	Not Listed.
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed.
n-Butane	
Louisiana Right-To-Know:	Not Listed.
California Proposition 65:	Not Listed.
New Jersey Right-To-Know:	SN 0273
Pennsylvania Right-To-Know:	Present
Massachusetts Right-To Know:	Present

Florida Substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic; Flammable
Michigan Critical Materials Register List:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed.
California - Regulated Carcinogens:	Not Listed.
Pennsylvania RTK - Special Hazardous Substances:	Not Listed.
New Jersey - Special Hazardous Substances:	Flammable - fourth degree
New Jersey - Environmental Hazardous Substances List:	SN 0273 TPQ: 500 lb
Illinois - Toxic Air Contaminants	Not Listed.
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed.
Ethane	
Louisiana Right-To-Know:	Not Listed.
California Proposition 65:	Not Listed.
New Jersey Right-To-Know:	SN 0834
Pennsylvania Right-To-Know:	Present
Massachusetts Right-To Know:	Present
Florida Substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic
Michigan Critical Materials Register List:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed.
California - Regulated Carcinogens:	Not Listed.
Pennsylvania RTK - Special Hazardous Substances:	Not Listed.
New Jersey - Special Hazardous Substances:	Flammable - fourth degree
New Jersey - Environmental Hazardous Substances List:	SN 0834 TPQ: 500 lb
Illinois - Toxic Air Contaminants	Not Listed.
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed.
Methane	
Louisiana Right-To-Know:	Not Listed.
California Proposition 65:	Not Listed.
New Jersey Right-To-Know:	SN 1202
Pennsylvania Right-To-Know:	Present
Massachusetts Right-To Know:	Present
Florida Substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic
Michigan Critical Materials Register List:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed.
California - Regulated Carcinogens:	Not Listed.
Pennsylvania RTK - Special Hazardous Substances:	Not Listed.
New Jersey - Special Hazardous Substances:	Flammable - fourth degree
New Jersey - Environmental Hazardous Substances List:	SN 1202 TPQ: 500 lb
Illinois - Toxic Air Contaminants	Not Listed.
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed.
Sulfur containing compounds	
Louisiana Right-To-Know:	Not Listed.
California Proposition 65:	Not Listed.
New Jersey Right-To-Know:	SN 1757
Pennsylvania Right-To-Know:	Present
Massachusetts Right-To Know:	Present
Florida Substance List:	Not Listed.
Rhode Island Right-To-Know:	Listed
Michigan Critical Materials Register List:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed.

California - Regulated Carcinogens: Not Listed.
 Pennsylvania RTK - Special Hazardous Substances: Not Listed.
 New Jersey - Special Hazardous Substances: Not Listed.
 New Jersey - Environmental Hazardous Substances List: Not Listed.
 Illinois - Toxic Air Contaminants: Not Listed.
 New York - Reporting of Releases Part 597 - List of Hazardous Substances: Not Listed.

Canada DSL/NDL Inventory: This product and/or its components are listed either on the Domestic Substances List (DSL) or are exempt.

Canadian Regulatory Information: "This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the (M)SDS contains all the information required by the Controlled Products Regulations."

Name	Canada - WHMIS: Classifications of Substances:	Canada - WHMIS: Ingredient Disclosure:
Propane	A,B1	1%
Propylene	A,B1,D2B	1%
Isobutane	A,B1	1%
n-Butane	A,B1	1%
Ethane	A,B1	1%
Methane	A,B1	1%
Sulfur containing compounds	B4	1%



NOTE: Not Applicable.

16. OTHER INFORMATION

Prepared By Toxicology and Product Safety
Revision Date: 05/19/2015

Revision Note:
Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is intended as guidance for safe handling, use, processing, storage, transportation, accidental release, clean-up and disposal and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.